


ULTRA320
 S C S I

iX3-U12HR

3U Dual Xeon Rack Mount Server

Features

- Support for two Intel Xeon EM64T 5000/5100 Series Dual Core Processors
- Up to 32GB Memory
- 12 hot-swap U320 SCSI SCA Drive Bays
- On-board graphics
- Dual Gigabit Network Controller



The iX3-U12HR Intel Xeon Server is a dual processor 3U rack mount server and provides a cost effective solution for primary servers, database applications and storage servers and are ideal for those requiring a combination of high capacity storage, high performance and value for money in their rack mount servers. It can support dual Intel Xeon 5000/5100 series EM64T dual core processors. Up to 32GB RAM can be housed in the 8 memory slots, dual Gigabit network ports and on-board graphics come as standard. The iX3-U12HR can have up to twelve hot-swap U320 SCSI SCA hard disk drives and has an Ultra 320 SCSI RAID controller supporting RAID 0, 1, 5 and 10.

Specifications

Processor	Up to two Intel® Xeon® "Dempsey" / "Woodcrest" (1066Mhz/1333MHz FSB) processors: Dual-Core
Chipset	Intel® 5000P chipset , Intel® 6321ESB I/O Controller Hub + PXH-V, Winbond 83627HF Super I/O chip
Memory Type / Slots / Upgrade	DDR2 533/667 ECC Fully Buffered / Eight 240-pin DIMM sockets / Supports up to 32GB (memory must be installed in pairs)
Graphics	ATI® ES1000 controller; PCI interface 32MB frame buffer of video memory
Expansion Slots	(2) PCI-E x16 slots (each with x8 signal), (1) PCI-E x8 slot (with x4 signal), (2) PCI-X 64/133MHz slots, (5) total expansion cards supported, Optional IPMI 2.0 support
Optical Drive	Slim type DVD-ROM drive, Optional DVD-RW, slim type 1.44MB Floppy Drive
Hard Drive Controller	PCI-X U320 SCSI RAID controller supporting RAID 0, 1, 5 and 10 (occupies 1 x PCI-X expansion slot)
Storage	Up to 12 hot-swap U320 SCSI SCA hard drives
Network Controller	Integrated dual GbE LANs from ESB2, with Intel PHY network controller
External I/O Ports	Rear: (1) PS/2 Mouse & (1) keyboard ports, (2) USB 2.0 ports, (1) 15-pin VGA port, (1) one serial port, (2) GbE and (1) 10/100Mbps RJ-45 LAN ports Front: one USB 2.0 port
Chassis Dimensions	Dimensions (inch): 16.9" (W) x 26 "(D) x 5.2"(H) Dimensions (mm): 422 (W) x 660 (D) x 132 (H) – 3U Rackmount Chassis
Power Supply	EPS 12V, 3U, 650W 2+1 Redundant PSU - 100V~240V AC input
Rackmount Rails	Included
Warranty	3 Year Limited



UK

Broadberry Data Systems Ltd
 Integration House
 61 Bideford Avenue
 Perivale, UB6 7PP
Tel: +44 (0)20 8997 6000
 Fax: +44 (0) 20 8997 0199
Web: www.broadberry.co.uk

USA

Broadberry Data Systems LLC
 501 Silverside Road, #119
 Wilmington
 DE, 19809
Tel: +1 800 496 9918
 Fax: +1 302 295 1086
Web: www.broadberry.com